

OPL-SWAI-G0010PB-S120w

Unmanaged 10 Ports Full Gigabit PoE Switch 8*10/100/1000Base-TX PoE port (Data/Power)
2*10/100/1000Base-TX uplink RJ45 port (Data)



Общие сведения

10-Port Gigabit PoE switch, using high-quality high-speed network IC and the most stable PoE chip, The PoE port meets the 802.3af or 802.3at standard. This series of PoE switches can provide seamless connection for 10/100/1000M Ethernet, and the PoE power supply port can automatically detect and supply power to powered devices that comply with IEEE802.3af or IEEE802.3at standards, and non-PoE devices intelligently detect no power supply, only data is transferred. If you're looking for a reliable [AI Ethernet switch](#) with advanced functionality, this product is a strong option to consider.

Функциональные особенности

- 8 Gigabit PoE Ports + 2 Gigabit RJ45 Ports Uplink;
- Comply with IEEE 802.3, IEEE 802.3u,
- IEEE802.3ab, IEEE802.3z standards;
- Port 1 supports BT 90W;
- Ethernet port 10/100/1000M rate auto adaptive;
- Support Port Auto-flip (Auto MDI/MDIX);
- AI DIP Function
- N: Standard normal;
- V: Port isolation;
- S: Super mode, Extension 250M
- PoE Watchdog

Спецификация

Model No.	OPL-SWAI-G0010PB-S120w
Product Name	Unmanaged 10 Ports Full Gigabit PoE Switch
Fixed Port	8*10/100/1000Base-TX PoE port (Data/Power) 2*10/100/1000Base-TX uplink RJ45 port (Data)
PoE Ports	1 port supports IEEE802.3af/at/poe++/bt, max. 90W PoE out 2-8 port support IEEE802.3af/at, max. 30W/port, PoE out
PoE Pin	af/at: 12+ 36-; af/at/poe++/bt: 12+ 45+ 36- 78-
PoE Budget	Max. 120W
PoE Dog	Support PoE auto execution, detection and reset fault device, when PoE is on N: Standard normal V: Port isolation
DIP	S: Super mode, Extension 250M
Bandwidth	20Gbps
Packet Forwarding	14.88Mpps
MAC	2K
Buffer	2.5M
Transmission Distance	10BASE-T: Cat3,4,5 UTP (≤250 meters) 100BASE-TX: Cat5 or later UTP (150 meters) 1000BASE-TX: Cat6 or later UTP (150 meters)
LED Indicator	P: Power LED (over-power LED) Uplink: Link LED=10/100M Link, 1000M=Gigabit Link Port: Orange=PoE LED, Green=LAN Link LED V: Port isolation LED S: Super mode LED
Power	Built-in power AC: 100-240VAC, 50-60Hz, 1.5A, Max. 125W
Operating Temperature/Humidity	-10~+55°C; 5%~90% RH Non-condensation
Storage Temperature/Humidity	-40~+75°C; 5%~95% RH Non-condensation
Product/Packing (L*W*H)	Size 210mm*150mm*35mm /265mm*220mm*68mm
N.W/G. W (kg)	0.8kgs/1.2kgs
Package	550*455*365mm/24.45KGs/20PCs
Lightning Protection Level	6KV 8/20us; IP30
Installation	Desktop
Certificate	CE-EMC EN55032; CE-LVD EN62368; FCC Part 15 Class B; RoHS
Warranty	1 year

Информация для заказа

Модель	Описание
OPL-SWAI-G0010PB-S120w	Unmanaged 10 Ports Full Gigabit PoE Switch 8*10/100/1000Base-TX PoE port (Data/Power) 2*10/100/1000Base-TX uplink RJ45 port (Data)