

OPL-SWAI-G0204PB-R120w

Unmanaged 6 Port Gigabit AI PoE BT Switch 4*10/100/1000M PoE Port 2*1G SFP Uplink Port



Общие сведения

OPL-SWAI-G0204PB-R120w - 6-портовый гигабитный коммутатор AI PoE BT использует высококачественную высокоскоростную сетевую микросхему и самый стабильный чип PoE. Порт PoE соответствует стандартам 802.3af или 802.3at. Эта серия коммутаторов PoE обеспечивает бесперебойное подключение к Ethernet 10/100/1000 Мбит/с, а порт питания PoE автоматически определяет и подает питание на устройства, соответствующие стандартам IEEE802.3af или IEEE802.3at. Устройства без PoE автоматически обнаруживают отсутствие питания, передавая только данные.

Спецификация

Model No.	OPL-SWAI-G0204PB-R120w
Product Name	Unmanaged 6 Ports Full Gigabit PoE Switch
Power	Input: AC 100-240V, 50/60Hz
Ethernet	4*10/100/1000M PoE Port 2* Gigabit SFP Uplink Port
Switching Capacity	12Gbps
Throughput	8.928Mpps
Packet Buffer	1Mb
MAC Address	2K
Jumbo Frame	9216bytes
Transfer Mode	Store and forward
MTBF	100000 hour
Network Protocol	IEEE802.3 (10Base-T) IEEE802.3u (100Base-TX) IEEE802.3ab (1000Base-TX) IEEE802.3z (1000Base-FX) IEEE802.3x (Flow control)
PoE Protocol	IEEE802.3af (15.4W) IEEE802.3at (30W)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD), EN61000-4-4 (EFT), EN61000-4-5 (Surge) Shock: IEC 60068-2-27 Free Fall: IEC 60068-2-32 Vibration: IEC 60068-2-6
Network Medium	10Base-T: Cat3, 4, 5 or above UTP (≤100m) 100Base-TX: Cat5 or above UTP (≤100m) 1000Base-TX: Cat5 or above UTP (≤100m)
Optical Media	Multimode fiber: 50/125, 62.5/125, 100/140μm Single mode fiber: 8/125, 8.7/125, 9/125, 10/125μm
Security Certificate	CE, FCC, RoHS
Working Environment	Working Temperature: -20~50°C Storage Temperature: -40~85°C Working Humidity: 0%~90%, non-condensing Storage Humidity: 5%~90%, non-condensing Working Height: Maximum 10,000 feet Storage Height: Maximum 10,000 feet
PWR (Power Supply)	Lighting: Powered Un-Light: No Power
Mode (DIP)	Lighting: VLAN Un-Light: Default Flashing: Extend
1-6 Green (Link&Data)	Lighting: Connecting Flashing: Data Transmit

	Un-Light: Disconnect
DIP Switch	VLAN: Port isolation mode. In this mode, the PoE ports (1-4) of the switch cannot communicate with each other, and can only communicate with the UP-link port. Default: Normal mode, all port can communicate with each other, the transmission distance is within 100 meters Extend: Link extension mode, 3-4 ports PoE power supply and data transmission distance can be extended to 250 meters, the transmission rate becomes 10M
Structure Size	Product Dimension (L*W*H): 200*118*44mm Package Dimension (L*W*H): 245*190*60mm N.W: 0.6kg G.W: 0.9kg
Packing Info	Carton MEAS: 505*320*402mm Packing Qty: 20units Packing Weight: 19KG
Power Voltage	Input Voltage: AC 100-240 V Power supply: 52V/2.3A
Package List	Switch 1pc Power cord 1pc User manual 1pc Certification 1pc

Информация для заказа

Модель	Описание
OPL-SWAI-G0204PB-R120w	Unmanaged 6 Port Gigabit AI PoE BT Switch 4*10/100/1000M PoE Port 2*1G SFP Uplink Port