

Features

Multicast: IGMP v1/v2/v3, IGMP Snooping, IGMP Fast Leave, MVR, IGMP filter, Support for transparent passing of multicast traffic without IGMP, snooping in certain port and VLAN, PIM-DM/SM/SSM

IPv4: Static routing, RIP v1/v2, OSPF, Policy Based Routing(PBR), ECMP, BFD for static routing, RIP, OSPF

IPv6: IPv4/v6 dual stack, ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet, Ipv6 neighbor discovery, Path MTU discovery, MLD V1,MLD snooping, IPv6 Static Routing, RIPng, OSPFv3, Manual tunnel, ISATAP tunnel, 6-to-4 tunnel

DHCP: DHCP server, client, relay, snooping

MPLS: MCE

QoS: Traffic classification of port/L2~4 protocol headers/VLAN/CoS/DSCP, CAR traffic control, 802.1P/DSCP priority mapping and remark. Multiple queuing algorithms such as SP, WRR or SP+WRR, Tail-Drop, WRED,Traffic supervision and traffic shaping, 8 queues per port

Security: DDoS attack prevention, TCP-SYN/UDP/ARP Flood attack prevention, IEEE 802.1x authentication, multiple-user authentication, guest vlan, L2~L4 ACL, Anti-DOS/IP spoofing/TCP/ping/SYN/ICMP flood attacks, Broadcast/multicast/unknown-unicast storm-control, Port isolation, Port Security, MAC address limitation, IP+MAC+port binding, DHCP Snooping, DHCP Option 82, DAI(Dynamic ARP Inspection), IPSG(IP Source Guard), IEEE 802.1x certification, MAC-based authentication AAA, Radius, TACACS+, Multiple user privileges

Reliability: 802.3ad Static/LACP link aggregation, EAPS, G.8032 ERPS, ISSU, VRRP, GR for OSPF and BGP, BFD for OSPF and BGP, VSS virtual stacking system

Management: CLI: Console, Telnet, SSHv1/2, Web-GUI: HTTP, HTTPS/SSL, SNMP v1/v2c/v3, RMON, SNMP alarm/inform/traps, Upload and download of FTP/TFTP/SFTP files, Debugging, Syslog for alarm/notification/Command/debug, Web-GUI: HTTP, HTTPS/SSL, NTP, SPAN, RSPAN (1:1 and N:1 mirror), LLDP, LLDP-MED, sFLOW , ZTP(Zero Touch Provisioning), Optical DDM, Ethernet cable diagnosis, 802.3ah, 802.1ag

Environment: Operating temperature/humidity: 0°C +50°C ,10%-90% non-condensing,
Storage temperature/humidity: -20°C +70°C , 5%-95% non-condensing

Characteristics

Advanced Hardware Architecture, Cutting Edge Processing Capability

- 1U pizza-box switch realizes the ultra-high port density of 24x2.5G RJ45 ports, 6x10G SFP+ ports. Equipped with high-performance ASIC switch chips, it can meet the application requirements of various complex scenarios.
- Doubled performance: The virtualized system makes full use of every link between physical devices, avoiding the link congestion of the traditional networking model Spanning Tree Protocol, making the best use of devices, doubling the performance, and protecting the original link investment to the greatest extent.
- High reliability: Based on advanced distributed processing technology, the efficient cross-physical device link aggregation function separates the logical control plane, service control plane and service data plane, providing uninterrupted Layer 3 routing and forwarding and avoiding business interruption caused by the single failure. Therefore, the reliability of the virtual system is greatly improved.
- Easy management: The entire virtual system realizes unified management of a single IP, and physical devices are visible to users, which simplifies the management of network devices and network topology, greatly improves operation efficiency, and effectively reduces operation and maintenance costs.

Innovative VSS

- Supports innovative Virtual Switch System (VSS), which can virtualize multiple physical devices into one logical device with unparalleled performance, reliability, and management compared to stand-alone physical devices.

Carrier-level High Reliability

- Supports STP/RSTP/MSTP, VRRP, ring network protection, dual uplink active/standby link protection, LACP and other simple and efficient redundancy protection mechanisms.
- Supports In-Service Software Upgrade (ISSU), ensuring the unremitting data forwarding during system upgrade.
- The ultra-high-precision BFD mechanism, through linkage with Layer 2 and Layer 3 protocols, realizes millisecond-level fault detection and service recovery, which greatly improves the reliability of the network system.
- Perfect Ethernet OAM mechanism, supporting 802.3ah and 802.1ag, realizes rapid detection and location of faults through real-time monitoring of network operation status.
- The high reliability hardware and software meet the fault recovery time requirement of 50ms for carrier-level services, and truly achieve the high reliability (99.999%) of carrier-class core devices.

Rich Service Features

- Perfect Layer 2 and Layer 3 multicast routing protocols meet the access requirements of IPTV, multi-terminal high-definition video surveillance and video conferencing;
- Complete Layer 3 routing protocols and large routing table capacity meet the needs of various network interconnection, and can built up ultra-large campus network, enterprise network and industry private network.

Comprehensive IPv6 Solutions

- Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, DHCPv6, etc.
- Supports Ping, Traceroute, Telnet, SSH, ACL and so on, meeting IPv6 networks' device management and service control requirements.
- Supports IPv6 multicast features such as MLD, MLD Snooping, IPv6 static routing, IPv6 Layer 3 routing protocols such as RIPng, OSPFv3, BGP4+, providing complete IPv6 Layer 2 and Layer 3 solutions.
- Supports a wealth of IPv4 to IPv6 transition technologies, including: IPv6 manual tunnel, automatic tunnel, 6to4 tunnel, and ISATAP tunnel to ensure the smooth transition from IPv4 network to IPv6 network.

Perfect Security Mechanisms

- Equipment-level security: The advanced hardware infrastructure design realizes the level-based packet schedule and packet protection, prevents DoS-/TCP-related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions.
- Perfect security authentication mechanisms: IEEE 802.1x, Radius and TACACS+.
- Enhanced service security mechanism: Supports clear text or MD5 authentication of related routing protocols, and Unicast Reverse Path Forwarding (uRPF), which can effectively control illegal services; supports in-depth detection and filtering of control packets and data packets, thereby effectively isolating illegal data packets and improving the security of the network system.

Innovative Eco-friendly Design

- Intelligent power management system: it adopts advanced power system architecture design to achieve efficient power conversion, unique power monitoring, slow start function, real-time monitoring of the running status, intelligent adjustment, and deep energy saving.
- Intelligent fan management system: Intelligent fan design supports automatic speed regulation, effectively reduces the speed, reduces noise, and prolongs the service life of the fan.
- Supports energy efficient Ethernet function and complies with the international standard IEEE 802.3az EEE, effectively reducing energy consumption.

Specifications

Model No.	OPL-SWM3-DC10G06X2.5G24PB
Backplane	240Gbps
Forwarding	180Mpps
MAC Table	32K
Ports	24xGE/2.5GE PoE+ ports, 4xGE/10GE SFP+ ports 1-8ports support IEEE802.3af/at/PoE++/bt Max.90W 9-24ports support IEEE802.3af/at Max.30W
Dimensions mm (W×D×H)	440×210×44mm
Power Supply	AC: 100V-240V, 50/60Hz DC: 36~72V
Power consumption	<740W
Total output BTU	2901
Noise@25° C(dBA)	45
MTBF(H)	>200,000
Forwarding mode	Store-forward
Flash (MB)	16
DRAM (MB)	512
Buffer size(MB)	2
Jumbo frame	9K
Routing table	IPv4: 8K IPv6: 4K
ARP table	IPv4: 12K IPv6: 2K
Total SVI	1K

Optical Modules

Gigabit Optical Modules

OPL-OT-GTA-RJ45	Gigabit SFP-to-RJ45 module
OPL--OT-GMM8-05	Gigabit SFP multi-mode, 500m, 850nm, LC, DDM
OPL-OT-G3-10	Gigabit SFP single mode, 10km, 1310nm, LC, DDM
OPL-OT-G3-20	Gigabit SFP single mode, 20km, 1310nm, LC, DDM

OPL-OT-G3-40	Gigabit SFP single mode, 40Km, 1310nm, LC, DDM
OPL-OT-G5-80	Gigabit SFP single mode, 80km, 1550nm, LC, DDM
OPL-OT-G5-120	Gigabit SFP single mode, 120km, 1550nm, LC, DDM
OPL-OT-GBD35-10	Gigabit SFP Bidi, 10km, Tx1310/Rx1550, LC, DDM
OPL-OT-GBD53-10	Gigabit SFP Bidi, 10km, Tx1550/Rx1310, LC, DDM
OPL-OT-GBD35-20	Gigabit SFP Bidi, 20km, Tx1310/Rx1550, LC, DDM
OPL-OT-GBD53-20	Gigabit SFP Bidi, 20km, Tx1550/Rx1310, LC, DDM
OPL-OT-GBD35-40	Gigabit SFP Bidi, 40km, Tx1310/Rx1550, LC, DDM
OPL-OT-GBD53-40	Gigabit SFP Bidi, 40km, Tx1550/Rx1310, LC, DDM
OPL-OT-GBD45-80	Gigabit SFP Bidi, 80km, Tx1490/Rx1550, LC, DDM
OPL-OT-GBD54-80	Gigabit SFP Bidi, 80km, Tx1550/Rx1490, LC, DDM
OPL-OT-GBD45-120	Gigabit SFP Bidi, 120km, Tx1490/Rx1550, LC, DDM
OPL-OT-GBD54-120	Gigabit SFP Bidi, 120km, Tx1550/Rx1490, LC, DDM
10GE Optical Modules	
OPL-OT-10GMM8-03	10GE SFP+ multi-mode, 300m, 850nm, LC, DDM
OPL-OT-10G3-10	10GE SFP+ single mode, 10km, 1310nm, LC, DDM
OPL-OT-10G3-20	10GE SFP+ single mode, 20km, 1310nm, LC, DDM
OPL-OT-10G3-40	10GE SFP+ single mode, 40km, 1310nm, LC, DDM
OPL-OT-10G5-40	10GE SFP+ single mode, 40Km, 1550nm, LC, DDM
OPL-OT-10G5-80	10GE SFP+ single mode, 80Km, 1550nm, LC, DDM
OPL-AOC-OM3-1	10G, SFP+ to SFP+ AOC, OM3, 1Meter
OPL-OT-10GBD23-10	10GE SFP+ Bidi, 10km, Tx1270/Rx1310, LC, DDM
OPL-OT-10GBD32-10	10GE SFP+ Bidi, 10km, Tx1310/Rx1270, LC, DDM
OPL-OT-10GBD23-20	10GE SFP+ Bidi, 20km, Tx1270/Rx1310, LC, DDM
OPL-OT-10GBD32-20	10GE SFP+ Bidi, 20km, Tx1310/Rx1270, LC, DDM
OPL-OT-10GBD23-40	10GE SFP+ Bidi, 40km, Tx1270/Rx1310, LC, DDM
LA-OT-10GBD32-40	10GE SFP+ Bidi, 40km, Tx1310/Rx1270, LC, DDM

Информация для заказа

Модель	Описание
OPL-SWM3-DC10G06X2.5G24PB	Multi-Gigabit L3 Managed Switch 24Port 1G/2.5G RJ45 PoE, Uplink 6Port 10G SFP+, AC-220V power supply, Cooling fan, 1U, standard 19-inch rack-mounted installation